




ORIGINALS

New Generation Flooring

**ORIGINALS SERIES
SPC FLOORING
TECHNICAL DATA SHEET**

DECOR		PACKAGE	PALETTE
PLANK		 9 Pieces = 2.503 m ² = 21,029 kg	 44 Package = 110,151 m ² = 945,271 kg
DECOR		PACKAGE	PALETTE
HERRINGBONE		 16 Pieces = 1.800 m ² = 15,120 kg	 63 Package = 113,400 m ² = 972,560 kg

Production Identification		Area Spc Flooring	
Surface Integrity Test		Embossed In Register / Microbevel	
Construction		Vinyl decor with SPC core, pre-attached IXPE and scratch coating	
Material - Core		Endure Core SPC - Stone Polymer Composite 2000 kg/m ³ density	
Protection		Ultimate Shield, Scratch, Stain and Wear Resistant - Surface Coating	
Surface Treatment		UV	
Usage		Residential - Commerical	
Warranty Period		Residential 20 years - Commercial 7 years	
Joint		Uniclic for Plank / Unidrop for Herringbone	
Installation Method		Were fixed mechanically to the substrate	
Underlay		IXPE	1 mm (Kg/m ³ 100)

General Requirements	EN16511	Specification
Wear Layer Thickness		0.50 mm
Total Thickness		4+1 mm
Length		750-1220 mm
Width		150-228 mm
Length and Width of Squared Elements		pass
Squareness		≤0.20 mm
Straightness		≤0.30 mm
Flatness Crosswise		concave ≤0.15% convex ≤0.20%
Flatness Lenghtwise		concave ≤0.50% convex ≤1%
Openings		average ≤0.15 mm max ≤0.20 mm
Height Difference		average ≤0.10 mm max ≤0.15 mm
Dimensional Stability and Curl		≤0.15 mm %1 ≤2 mm

Classifaction Surface Performance	EN16511	Specification
Class	 EN ISO 10874	Class 23-31-32-33-34
Wear Resistance Method A - Taber Test	 EN 24338 Procedure A:2013	Class 34
Micro Scratch Resistance (Class) For Mat Surfaces (Gloss)	 TS EN 16094 (Metot A)	Class 34
Impact Resistance (big ball)	 EN 13329:2006+A1:2008 Annex F	Class 34
Castor Chair Test	 EN ISO 4918	Class 34
Effect of Furniture Leg	 ISO 16581, tested with foot type 0]	Class 34
Residual Indentation	 EN ISO 24343-1	Class 34
Resistance to Staining	 EN438-2 +A1	Grade for group 1,2,3
Flexibility Categories	 EN ISO 178:2019	High rigidity
Light Fastness	 EN ISO 105-B02:2014	≥6
Locking Strength (kN/m)	 ISO 24334	Class 34

Product Performance - Physical Behaviour

EN14041

Specification

Slide Resistance



TS EN 13893

DS

Fire Behavior



TS EN 13501-1

Bfl S1

Thermal Resistance



ISO 8302

0,0311 M2k/w

Thermal Conductivity



EN 12667

0,296 W/(m.K)

Floor Heating System



suitable

max 27

Electrostatics Behaviour



EN 1815:2016

antistatics floor covering

Enviroment

EN14041

Specification

Emission of Forhaldehyde



EN 717-1:2004

E1

Antibacterial



ISO22196

Pass

Phatalate Analysis



Inhouse Method

Phatalate Free

VOC Emissions Class - (French Regulation)



French VOC Regulation

A+

VOC Emission - Indoor Air Comfort Gold



French VOC Regulation

E1

VOC Emission - M1



M1 Protocol of November 2017

Pass

VOC Emission - CDPH



CDPH/EHLB/Std Method V1.2. Jan17

Pass

More Test

IIC - ASTM E492-22

70

STC - ASTM E90-23

75

European Directive Limiting the VOC Concent in Certain Products, 2004/42/EC

Pass



FloorScore® Standard
Indoor Air quality Certified to SCS-105 Version 4.2 – 2023

AREA FLOORS PRODUCTION : Ömerli Mahallesi, Ilgaz Sokak, No: 7/1, Arnavutköy, İstanbul / Türkiye

AREA FLOORS EUROPE : Gietijzerstraat 20 3534AV Utrecht The Netherlands

T : +90 (212) 741 51 61 info@areafloors.com.tr

www.areafloors.com.tr





ORIGINALS

New Generation Flooring

ORIGINALS SERIES
SPC FLOORING
TECHNICAL DATA SHEET